

# Safety Data Sheet

## THERMOTEK X99 SILICONE HIGH SLOPE

Revision date : 2018/10/19  
Version: 1.0

Page: 1/10  
(30686890/SDS\_GEN\_CA/EN)

### 1. Identification

#### Product identifier used on the label

## THERMOTEK X99 SILICONE HIGH SLOPE

#### Recommended use of the chemical and restriction on use

Recommended use\*: Product for construction chemicals  
Recommended use\*: Use in Coatings

\* The "Recommended use" identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

#### Details of the supplier of the safety data sheet

##### Company:

BASF Canada Inc.  
100 Milverton Drive  
Mississauga, ON L5R 4H1, CANADA

Telephone: +1 289 360-1300

#### Emergency telephone number

CANUTEC (reverse charges): (613) 996-6666  
BASF HOTLINE: (800) 454-COPE (2673)

#### Other means of identification

Chemical family: No applicable information available.

---

### 2. Hazards Identification

#### According to Hazardous Products Regulations (HPR) (SOR/2015-17)

##### Classification of the product

Skin Sens.	1	Skin sensitization
Muta.	1B	Germ cell mutagenicity
Carc.	1B	Carcinogenicity
STOT RE	1 (by inhalation)	Specific target organ toxicity — repeated exposure
Aquatic Acute	3	Hazardous to the aquatic environment - acute
Aquatic Chronic	3	Hazardous to the aquatic environment - chronic

# Safety Data Sheet

## THERMOTEK X99 SILICONE HIGH SLOPE

Revision date : 2018/10/19  
Version: 1.0

Page: 2/10  
(30686890/SDS\_GEN\_CA/EN)

### Label elements

Pictogram:



Signal Word:  
Danger

Hazard Statement:

H317	May cause an allergic skin reaction.
H350	May cause cancer.
H340	May cause genetic defects.
H372	Causes damage to organs (Lung) through prolonged or repeated exposure (inhalation).
H402	Harmful to aquatic life.
H412	Harmful to aquatic life with long lasting effects.

Precautionary Statements (Prevention):

P280	Wear protective gloves/protective clothing/eye protection/face protection.
P201	Obtain special instructions before use.
P260	Do not breathe dust/gas/mist/vapours.
P202	Do not handle until all safety precautions have been read and understood.
P273	Avoid release to the environment.
P270	Do not eat, drink or smoke when using this product.
P264	Wash with plenty of water and soap thoroughly after handling.
P272	Contaminated work clothing should not be allowed out of the workplace.

Precautionary Statements (Response):

P314	Get medical advice/attention if you feel unwell.
P308 + P311	IF exposed or concerned: Call a POISON CENTER or doctor/physician.
P303 + P352	IF ON SKIN (or hair): Wash with plenty of soap and water.
P362 + P364	Take off contaminated clothing and wash it before reuse.

Precautionary Statements (Storage):

P405	Store locked up.
------	------------------

Precautionary Statements (Disposal):

P501	Dispose of contents/container to hazardous or special waste collection point.
------	---

### Hazards not otherwise classified

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

Labeling of special preparations (GHS):

Product contains the following components and may cause an allergic skin reaction: 1,2-Ethanediamine, N-[3-(trimethoxysilyl)propyl]-

# Safety Data Sheet

## THERMOTEK X99 SILICONE HIGH SLOPE

Revision date : 2018/10/19  
Version: 1.0

Page: 3/10  
(30686890/SDS\_GEN\_CA/EN)

### 3. Composition / Information on Ingredients

#### According to Hazardous Products Regulations (HPR) (SOR/2015-17)

<u>CAS Number</u>	<u>Weight %</u>	<u>Chemical name</u>
64742-48-9	>= 0.3 - < 1.0%	Naphtha (petroleum), hydrotreated heavy
1760-24-3	>= 0.0 - < 1.0%	1,2-Ethanediamine, N-[3-(trimethoxysilyl)propyl]-
14808-60-7	>= 10.0 - < 15.0%	Quartz (SiO <sub>2</sub> )
13463-67-7		Titanium dioxide
14808-60-7		Quartz (SiO <sub>2</sub> )

### 4. First-Aid Measures

#### Description of first aid measures

##### General advice:

First aid personnel should pay attention to their own safety. Remove contaminated clothing.

##### If inhaled:

No applicable information available.

##### If on skin:

Wash thoroughly with soap and water. Under no circumstances should organic solvent be used. If irritation develops, seek medical attention.

##### If in eyes:

Wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

##### If swallowed:

Rinse mouth and then drink 200-300 ml of water. Do not induce vomiting.

#### Most important symptoms and effects, both acute and delayed

Symptoms: The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11.

Hazards: No applicable information available.

#### Indication of any immediate medical attention and special treatment needed

##### Note to physician

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

### 5. Fire-Fighting Measures

#### Extinguishing media

Suitable extinguishing media:

foam, water spray, dry powder, carbon dioxide

# Safety Data Sheet

## THERMOTEK X99 SILICONE HIGH SLOPE

Revision date : 2018/10/19  
Version: 1.0

Page: 4/10  
(30686890/SDS\_GEN\_CA/EN)

Unsuitable extinguishing media for safety reasons:  
water jet

### Special hazards arising from the substance or mixture

Hazards during fire-fighting:  
harmful vapours, nitrogen oxides, fumes/smoke, carbon black, carbon oxides  
See MSDS section 10 - Stability and reactivity.

### Advice for fire-fighters

Protective equipment for fire-fighting:  
Wear a self-contained breathing apparatus.

### Further information:

The degree of risk is governed by the burning substance and the fire conditions. Contaminated extinguishing water must be disposed of in accordance with official regulations.

---

## 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

Use personal protective clothing. Handle in accordance with good building materials hygiene and safety practice.

### Environmental precautions

Contain contaminated water/firefighting water. Do not discharge into drains/surface waters/groundwater.

### Methods and material for containment and cleaning up

For small amounts: Sweep/shovel up. Dispose of absorbed material in accordance with regulations.  
For large amounts: Sweep/shovel up. Dispose of absorbed material in accordance with regulations.

---

## 7. Handling and Storage

### Precautions for safe handling

Avoid contact with the skin, eyes and clothing.

### Protection against fire and explosion:

Keep away from sources of ignition - No smoking. The relevant fire protection measures should be noted.

### Conditions for safe storage, including any incompatibilities

No applicable information available.

Further information on storage conditions: Keep only in the original container in a cool, well-ventilated place. Protect from direct sunlight. Store protected against freezing.

---

## 8. Exposure Controls/Personal Protection

### Components with occupational exposure limits

Titanium dioxide	OSHA PEL	PEL 15 mg/m <sup>3</sup> Total dust ; TWA value 10 mg/m <sup>3</sup> Total dust ;
	ACGIH TLV	TWA value 10 mg/m <sup>3</sup> ;

# Safety Data Sheet

## THERMOTEK X99 SILICONE HIGH SLOPE

Revision date : 2018/10/19  
Version: 1.0

Page: 5/10  
(30686890/SDS\_GEN\_CA/EN)

Quartz (SiO <sub>2</sub> )	OSHA PEL	TWA value 0.1 mg/m <sup>3</sup> Respirable dust ; TWA value 0.1 mg/m <sup>3</sup> Respirable ; The exposure limit is calculated from the equation, $10\text{mg}/\text{m}^3/(\%\text{SiO}_2+2)$ , using a value of 100% SiO <sub>2</sub> . Lower percentages of SiO <sub>2</sub> will yield higher exposure limits. TWA value 2.4 millions of particles per cubic foot of air Respirable ; The exposure limit is calculated from the equation, $250/(\%\text{SiO}_2+5)$ , using a value of 100% SiO <sub>2</sub> . Lower percentages of SiO <sub>2</sub> will yield higher exposure limits.
	ACGIH TLV	TWA value 0.025 mg/m <sup>3</sup> Respirable fraction ;
Quartz (SiO <sub>2</sub> )	OSHA PEL	TWA value 0.1 mg/m <sup>3</sup> Respirable dust ; TWA value 0.1 mg/m <sup>3</sup> Respirable ; The exposure limit is calculated from the equation, $10\text{mg}/\text{m}^3/(\%\text{SiO}_2+2)$ , using a value of 100% SiO <sub>2</sub> . Lower percentages of SiO <sub>2</sub> will yield higher exposure limits. TWA value 2.4 millions of particles per cubic foot of air Respirable ; The exposure limit is calculated from the equation, $250/(\%\text{SiO}_2+5)$ , using a value of 100% SiO <sub>2</sub> . Lower percentages of SiO <sub>2</sub> will yield higher exposure limits.
	ACGIH TLV	TWA value 0.025 mg/m <sup>3</sup> Respirable fraction ;

### Advice on system design:

No applicable information available.

### Personal protective equipment

#### Hand protection:

Wear chemical resistant protective gloves.

#### Eye protection:

Safety glasses with side-shields.

#### Body protection:

Body protection must be chosen based on level of activity and exposure.

#### General safety and hygiene measures:

Avoid contact with the skin, eyes and clothing. No special measures necessary if stored and handled correctly. Handle in accordance with good building materials hygiene and safety practice. Wearing of closed work clothing is recommended. When using, do not eat, drink or smoke. Hands and/or face should be washed before breaks and at the end of the shift. At the end of the shift the skin should be cleaned and skin-care agents applied. Gloves must be inspected regularly and prior to each use. Replace if necessary (e.g. pinhole leaks).

---

## 9. Physical and Chemical Properties

Form: dispersion  
Odour: of the solvent contained in the product

# Safety Data Sheet

## THERMOTEK X99 SILICONE HIGH SLOPE

Revision date : 2018/10/19  
Version: 1.0

Page: 6/10  
(30686890/SDS\_GEN\_CA/EN)

Odour threshold:	No applicable information available.
Colour:	white
pH value:	No applicable information available.
Melting point:	No applicable information available.
Boiling point:	No applicable information available.
Sublimation point:	No applicable information available.
Flash point:	No applicable information available.
Flammability:	No applicable information available.
Lower explosion limit:	No applicable information available.
Upper explosion limit:	No applicable information available.
Autoignition:	No applicable information available.
Vapour pressure:	No applicable information available.
Density:	1.28 - 1.32 g/cm <sup>3</sup> (approx. 20 °C)
Relative density:	No applicable information available.
Vapour density:	No applicable information available.
Partitioning coefficient n-octanol/water (log Pow):	No applicable information available.
Thermal decomposition:	No decomposition if stored and handled as prescribed/indicated.
Viscosity, dynamic:	No applicable information available.
Viscosity, kinematic:	No applicable information available.
Solubility in water:	No applicable information available.
Solubility (quantitative):	No applicable information available.
Solubility (qualitative):	No applicable information available.
Evaporation rate:	No applicable information available.
Other Information:	If necessary, information on other physical and chemical parameters is indicated in this section.

---

## 10. Stability and Reactivity

### Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

### Chemical stability

The product is stable if stored and handled as prescribed/indicated.

### Possibility of hazardous reactions

The product is stable if stored and handled as prescribed/indicated.

### Conditions to avoid

See MSDS section 7 - Handling and storage.

### Incompatible materials

strong acids, strong bases, strong oxidizing agents, strong reducing agents

### Hazardous decomposition products

Decomposition products:

No hazardous decomposition products if stored and handled as prescribed/indicated.

Thermal decomposition:

No decomposition if stored and handled as prescribed/indicated.

---

# Safety Data Sheet

## THERMOTEK X99 SILICONE HIGH SLOPE

Revision date : 2018/10/19  
Version: 1.0

Page: 7/10  
(30686890/SDS\_GEN\_CA/EN)

### 11. Toxicological information

#### Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

#### Acute Toxicity/Effects

##### Acute toxicity

Assessment of acute toxicity: Virtually nontoxic after a single ingestion. Based on available Data, the classification criteria are not met.

##### Oral

No applicable information available.

##### Inhalation

No applicable information available.

##### Dermal

No applicable information available.

##### Assessment other acute effects

Based on available Data, the classification criteria are not met.

##### Irritation / corrosion

Assessment of irritating effects: No irritation is expected under intended use and appropriate handling. Based on available Data, the classification criteria are not met.

##### Sensitization

Assessment of sensitization: May cause sensitization by skin contact.

##### Aspiration Hazard

No aspiration hazard expected.

#### Chronic Toxicity/Effects

##### Repeated dose toxicity

Assessment of repeated dose toxicity: This product contains crystalline silica (quartz). Prolonged or repeated inhalation of respirable crystalline silica may result in silicosis.

##### Genetic toxicity

Assessment of mutagenicity: Capable of causing genetic defects.

##### Carcinogenicity

Assessment of carcinogenicity: May cause cancer.

##### *Information on: Titanium dioxide*

*Assessment of carcinogenicity: IARC (International Agency for Research on Cancer) has classified this substance as group 2B (The agent is possibly carcinogenic to humans). In long-term studies in rats in which the substance was given by inhalation, a carcinogenic effect was observed. Tumors were only observed in rats after chronic inhalative exposure to high concentrations which caused sustained lung inflammation. In long-term studies in rats and mice in which the substance was given by feed, a carcinogenic effect was not observed. Dermal exposure is not expected to be carcinogenic.*

##### *Information on: Quartz (SiO<sub>2</sub>)*

# Safety Data Sheet

## THERMOTEK X99 SILICONE HIGH SLOPE

Revision date : 2018/10/19  
Version: 1.0

Page: 8/10  
(30686890/SDS\_GEN\_CA/EN)

*Assessment of carcinogenicity: In long-term studies in rats and mice in which the substance was given by feed, a carcinogenic effect was not observed. In long-term animal studies in which the substance was given by inhalation in high doses, a carcinogenic effect was observed. The substance and its compounds in the form of respirable dusts/aerosols classified by the German MAK commission as a category 1 carcinogen (substances that cause cancer to humans). A carcinogenic effect cannot safely be ruled out. The inhalation uptake of the alveolar fraction of the fine dust may cause damage to the lungs. The International Agency for Research on Cancer (IARC) has classified this substance as a Group 1 (known) human carcinogen.  
NTP listed carcinogen*

-----

### Reproductive toxicity

Assessment of reproduction toxicity: The chemical structure does not suggest a specific alert for such an effect. Based on available Data, the classification criteria are not met.

### Teratogenicity

Assessment of teratogenicity: The chemical structure does not suggest a specific alert for such an effect. Based on available Data, the classification criteria are not met.

### Other Information

Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses. The product has not been tested. The statements on toxicology have been derived from the properties of the individual components.

## **Symptoms of Exposure**

The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11.

---

## **12. Ecological Information**

### **Toxicity**

#### Aquatic toxicity

Assessment of aquatic toxicity:

Acutely harmful for aquatic organisms. May cause long-term adverse effects in the aquatic environment.

### **Persistence and degradability**

#### Assessment biodegradation and elimination (H<sub>2</sub>O)

Inherently biodegradable. The insoluble fraction can be removed by mechanical means in suitable waste water treatment plants.

The polymer component of the product is poorly biodegradable.

### **Bioaccumulative potential**

#### Assessment bioaccumulation potential

Discharge into the environment must be avoided.

### **Mobility in soil**

#### Assessment transport between environmental compartments

No data available.



# Safety Data Sheet

## THERMOTEK X99 SILICONE HIGH SLOPE

Revision date : 2018/10/19  
Version: 1.0

Page: 9/10  
(30686890/SDS\_GEN\_CA/EN)

### Additional information

Other ecotoxicological advice:

Do not discharge product into the environment without control. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

---

### 13. Disposal considerations

#### Waste disposal of substance:

Dispose of in accordance with local authority regulations. Do not discharge into drains/surface waters/groundwater.

---

### 14. Transport Information

#### Land transport

TDG

Not classified as a dangerous good under transport regulations

#### Sea transport

IMDG

Not classified as a dangerous good under transport regulations

#### Air transport

IATA/ICAO

Not classified as a dangerous good under transport regulations

---

### 15. Regulatory Information

#### Federal Regulations

#### Registration status:

Chemical DSL, CA released / listed

#### NFPA Hazard codes:

Health: 2 Fire: 0 Reactivity: 0 Special:

---

### 16. Other Information

#### SDS Prepared by:

BASF NA Product Regulations  
SDS Prepared on: 2018/10/19

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our

# Safety Data Sheet

## THERMOTEK X99 SILICONE HIGH SLOPE

Revision date : 2018/10/19  
Version: 1.0

Page: 10/10  
(30686890/SDS\_GEN\_CA/EN)

---

operations on society and the environment during production, storage, transport, use and disposal of our products.

---

END OF DATA SHEET